

Cassette (60 x 60) Type


Semi FS

Compact Design Allows Space Saving!



Features

- Anti-Mould, One Touch Air Filter
- Odour-Removing Function
- Removable, Washable Panel
- Quiet Mode
- Powerful Mode
- Soft Dry Operation Mode
- Airflow Direction Control (Up & Down)
- Auto Chargeover
- Hot Start Control
- 24-Hour ON & OFF
- Random Auto Restart
- Long Piping 20m(E18:30m)
- Top Panel Maintenance Access
- Self-Diagnostic Function
- Super Alleru-Buster Filter (option)



Panel: CZ-BT20E

Specifications

Inverter Models



Cooling/Heating

Items	Cooling Capacity		Heating Capacity	Power Source **	Current	Power Input	EER COP	Annual Energy Consumption	Air Volume	Noise Level*				Dimensions			Net Weight			Piping Connection			Pipe Length			Operation Range (Outdoor)
	kW	Btu/h								Cooling Heating	Cooling Heating	Sound Pressure Level	Sound Power Level	Indoor (Hi/La/ S-La) Cooling Heating	Outdoor (Hi) Cooling Heating	Indoor (Hi) Cooling Heating	Outdoor (Hi) Cooling Heating	Indoor	Panel	Outdoor	Indoor	Panel	Outdoor	Gas Side	Liquid Side	
			W/W	m ³ /min	dB(A)	dB(A)	dB	dB	mm (H) (W) (D)																	
	Indoor Outdoor	kW	Btu/h	Phase V Hz	A	W	W/W	kWh	m ³ /min	dB(A)	dB(A)	dB	dB	mm (H) (W) (D)	mm (H) (W) (D)	mm (H) (W) (D)	kg	kg	kg	O.D. mm (inch)	O.D. mm (inch)	m	m	m	g/m	
CS-E10HB4EA CU-E10HBEA	2.50 (0.69-3.20) 6.530 (2,050-10,900)	3.20 (0.69-5.10) 10,900 (2,050-17,400)	1Φ 230-240 50	2.9 3.8	620 (148-870) 820 (125-1,450)	4.03A 3.90A	310	10.5 10.8	34/26/23 35/28/25	45 46	47 48	58 59	260 575 575	51 700 700	540 780/88" 289	18.0	2.5	35	9.52 (3/8")	6.35 (1/4")	3-20	15	10	20	-10-43 -10-24	
CS-E15HB4EA CU-E15HBEA	4.10 (0.90-4.80) 14,000 (3,070-16,400)	5.10 (0.90-6.20) 17,400 (3,070-21,100)	1Φ 230-240 50	6.0 8.0	1,300 (255-1,710) 1,770 (260-2,190)	3.15B 2.88D	650	10.5 10.8	34/26/23 35/28/25	45 47	47 48	58 60	260 575 575	51 700 700	750 875/68" 345	18.0	2.5	48	12.70 (1/2")	6.35 (1/4")	3-20	15	10	20	-10-43 -10-24	
CS-E18HB4EA CS-E18HBEA	4.60 (0.90-5.70) 16,400 (3,070-19,400)	5.60 (0.90-7.10) 19,100 (3,070-24,200)	1Φ 230-240 50	7.0 8.5	1,530 (255-1,930) 1,900 (260-2,450)	3.14B 2.95D	765	11.0 11.5	36/28/25 37/29/26	47 48	49 50	60 61	260 575 575	51 700 700	750 875/68" 345	18.0	2.5	48	12.70 (1/2")	6.35 (1/4")	3-30	20	10	20	-10-43 -10-24	
CS-E21HB4EAS CS-E21HBEA	5.90 (0.90-6.30) 23,100 (3,070-21,500)	7.00 (0.90-8.00) 23,900 (3,070-27,300)	1Φ 230-240 50	9.2 10.9	2,050 (255-2,200) 2,450 (260-2,820)	2.88C 2.86D	1,025	12.8 14.0	41/33/30 42/34/31	49 49	54 55	62 62	260 575 575	51 700 700	750 875/68" 345	18.0	2.5	50	12.70 (1/2")	6.35 (1/4")	3-30	20	10	20	-10-43 -10-24	